

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B01J 38/52, 38/04, 20/34	A1	(11) International Publication Number: WO 95/32801 (43) International Publication Date: 7 December 1995 (07.12.95)
(21) International Application Number: PCT/US95/06717 (22) International Filing Date: 30 May 1995 (30.05.95) (30) Priority Data: 08/252,012 1 June 1994 (01.06.94) US (71) Applicant: DREW CHEMICAL CORPORATION [US/US]; One Drew Chemical Plaze, Boonton, NJ 07005 (US). (72) Inventors: MANSFIELD, William, D.; 11543 Blackwater Road, Baker, LA 70714 (US). FORET, Todd, L.; 107 North Morein Street, Villa Platte, LA 70714 (US). VIDRINE, Hubert, P., Jr.; Route 1, Box 191, Opelousas, LA 70714 (US). (74) Agents: HEDDEN, David, L.; Ashland Chemical Company, P.O. Box 2219, Columbus, OH 43216 (US) et al.		(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, MG, MN, MW, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: A PROCESS FOR IMPROVING THE EFFECTIVENESS OF A PROCESS CATALYST (57) Abstract This invention relates to a process for improving the effectiveness of a refinery process catalyst. The process comprises treating the refinery process catalyst with an effective amount of reducing agent selected from the group consisting of hydrazine, oximes, hydroxylamines, carbohydrazide, erythorbic acid, and mixtures thereof.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

**A PROCESS FOR IMPROVING THE EFFECTIVENESS
OF A PROCESS CATALYST**

TECHNICAL FIELD

5 This invention relates to a process for improving the effectiveness of a process catalyst. The process comprises treating the process catalyst with a reducing agent selected from the group consisting of hydrazine, oximes, hydroxylamines, carbohydrazide, erythorbic acid,
10 and mixtures thereof.

BACKGROUND OF THE INVENTION

 Catalytic reforming is used in the refining of crude oil to increase the yield of higher octane gasoline which
15 sells at higher prices. In catalytic reforming, the paraffins and naphthenes are passed through the reformer with the goal of minimizing cracking. Instead their structure is rearranged to form higher octane aromatics. Essentially catalytic reforming converts low octane
20 paraffins to naphthenes. Naphthenes are converted to higher octane aromatics. Aromatics are left essentially unchanged.

 Refineries generally use a platinum catalyst or platinum alloy supported on a silica or silica-aluminum
25 substrate as the reforming catalyst, although other catalysts, including the oxides of aluminum, chromium, molybdenum, cobalt, and silicon can be used.

 In the strong reducing environment and elevated temperatures (500°C to 600°C) of the reformer, the catalyst
30 becomes contaminated with metals, such as lead, iron, nickel, vanadium, sulfur compounds, arsenic, and coke. The result is that the catalyst becomes inactive and the efficiency of the reformer decreases. In order to reduce contamination of the reformer catalyst, most reformer
35 catalysts have a guard bed for the catalyst which removes contaminants from the feed stream. Over a period of time,

-2-

contaminants still break through to the reformer catalyst and reduce catalytic activity.

As the activity of the catalyst decreases, the reaction temperature of the reformer is increased to maintain the desired output. Additionally, organic chloride containing compounds are fed to the reformer to reactivate the catalyst on a periodic basis or continuously at a low dosage. The activity of the reformer catalyst is a function of surface area, pore volume, active platinum and organic chloride content. The efficiency of the reformer is reduced during operation by coke deposition, chloride loss, and contaminants such as sulfur, lead, heavy metals, and oxygen.

When the catalyst becomes depleted, it is necessary to regenerate the catalyst. The activity of the catalyst can be restored by high temperature oxidation of the coke followed by chloriding. This regenerative process allows the reformer to operate for up to a 24 month period between regenerations. Normally the catalyst can be regenerated at least three times before it has to be replaced and returned to the manufacturer for reclamation.

SUMMARY OF THE INVENTION

This invention relates to a process for improving the effectiveness of a process catalyst which comprises:

treating said process catalyst with an effective amount of a reducing agent selected from the group consisting of hydrazine, oximes, hydroxylamines, carbohydrazide, erythorbic acid, and mixtures.

Indirect evidence and direct evidence indicates that the treatment of the process catalyst by the subject process reduces or retards the formation of metal contaminants, oxygen, sulfur, and coke on the process catalyst. Thus the process could be alternatively

-3-

characterized as a process for reducing and/or retarding the contamination of a process catalyst.

Reducing or retarding the contamination of the process catalyst results in the increased effectiveness of the reformer. This is shown by yields across the reformer, higher octane gasoline, and less benzene in the reformat. Moreover, since yields of higher octane gasoline are increased, the refinery can blend lower grade fuels into the gasoline. Furthermore, the reformer can also be operated at lower temperature and pressure thus minimizing coking and cracking while making the same octane gasoline and improving yield. Finally, the refinery can save money and time spent on catalyst regeneration by increasing the life of the catalyst and the time between regenerations.

Process catalysts which benefit from this treatment include reforming, hydrotreating, hydrocracking, isomerization, hydrogenation, and guard bed catalysts. Treating the process catalyst involves adding the reducing agent to a process stream which will enable the reducing agent to come into contact with the process catalyst. Examples of process streams which will provide such contact between the reducing agent and the process catalyst include stripper steam, crude overhead, naphtha, splitter feed, refining feed, and feedlines for chloriding chemicals used in the reformer.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of a simple refinery.

DEFINITIONS AND ABBREVIATIONS

BZE -- benzene.

CCAT -- catalyst contamination after treatment.

CCBT -- catalyst contamination before treatment.

-4-

CYH -- cyclohexane.

DREWCOR -- DREWCOR is a registered trademark of Ashland Oil, Inc. DREWCOR 2130 corrosion inhibitor is chemically defined as a blend of amines and MEKOR such
5 that the amount of MEKOR is about 5 percent by weight.

FEED POINT -- place where reducing agent is injected into the sulfur containing hydrocarbon process stream.

REFINERY PROCESS CATALYST -- a refinery process catalyst is a catalyst used in refining crude oil,
10 particularly catalysts used in the reforming of gasoline.

REFINERY PROCESS STREAM -- any refinery stream which comes into contact with a refinery process catalyst, particularly hydrocarbon streams which flow through the reformer of the refinery and come into contact with the
15 reformer catalyst, most particularly three phase refinery process streams which carry a liquid hydrocarbon phase, a gaseous hydrocarbon phase, and an aqueous phase.

MCP -- methyl cyclopentane.

MEKOR -- MEKOR is a registered trademark of Ashland
20 Oil, Inc. and is chemically defined as methyl ethyl ketoxime [$\text{H}_3\text{C}(\text{C}=\text{NOH})\text{CH}_2\text{CH}_3$].

MOTOR OCTANE NUMBER (MON) -- motor octane number measured by ASTM D-357 and is a guide to engine performance at high speeds or under heavy load conditions.

25 PETROLEUM PRODUCTS -- products produced by refining crude oil including gasoline, diesel fuel, propane, jet fuel, kerosene, propane, naphtha, benzene, gasoline, aniline, etc.

ppm -- parts per million MEKOR.

30 REFORMATE -- reformed aromatics, primarily naphtha, which is upgraded in octane by means of catalytic reforming.

RESEARCH OCTANE NUMBER (RON) -- research octane number measured by ASTM D-2699. A standardized test

-5-

engine operating under standardized conditions (600 rpm) is used. Results are comparable to those obtained in an automobile engine operated at low speed.

5 SAMPLE POINT -- place where a sample of a treated hydrocarbon stream is taken to determine if there was a reduction in catalyst contaminants.

SUM C₆ -- sum of compounds having 6 carbon atoms.

10
$$\frac{R + M}{2} = \text{average of RON and MON.}$$

YIELD -- a percentage calculated by subtracting the liquid weight of the product that comes out of the reformer from the liquid weight of the feed which goes into the reformer and then dividing by 100.

15

DETAILED DESCRIPTION OF DRAWING

FIG. 1 illustrates the flow chart of a simple refinery. It shows the sample points 1-12 for the process streams tested, feedpoints for MEKOR 21-27, storage tanks 31-34, reformers 41-44, vessels 51-61, boiler 71, and hydrogen flare 72. Raw untreated crude oil 31 is fed to the desalter 54 where it is desalted and pumped into the crude tower 51. From the crude tower, a crude gasoline fraction is pumped into the raw gas accumulator 53 and then to the splitter tower 55. Fractions of the separated gasoline are pumped from the splitter tower to the depropanizer 57, the reformer 41-44, and to the hydrogen separator 59. The fraction from the hydrogen separator is pumped to the stabilizer tower 60. MEKOR is fed into the process at feedpoints 21-27. Sample points include 1-12.

The specific components in Fig. 1 are identified as follows:

-6-

SAMPLE POINTS

1 RAW CRUDE
2 CRUDE OUT OF DESALTER
5 3 WATER OUT OF DESALTER
4 DIESEL TO STORAGE TANK
5 WATER OUT OF RAW GAS ACCUMULATOR
6 SPLITTER BOTTOMS
7 STABILIZER BOTTOMS
10 8 WATER OUT OF STABILIZER ACCUMULATOR
9 STABILIZER PROPANE
10 WATER OUT OF SPLITTER ACCUMULATOR
11 WATER OUT OF DEPROPANIZER ACCUMULATOR
12 DEPROPANIZER PROPANE

15

CHEMICAL FEED POINTS

21 MEKOR INTO RAW CRUDE
22 MEKOR INTO STRIPPING STEAM TO CRUDE TOWER
23 MEKOR INTO CRUDE TOWER REFLUX
20 24 DREWCOR 2130 INTO CRUDE TOWER REFLUX
25 MEKOR INTO SPLITTER TOWER FEED
26 1,1,1 TRICHLOROETHANE INTO REFORMATE FEED
27 MEKOR INTO REFORMERS

25

STORAGE TANKS

31 RAW CRUDE
32 DIESEL
33 GASOLINE
34 PROPANE

30

REFORMERS

41 REFORMER #1
42 REFORMER #2
43 REFORMER #3

-7-

44 REFORMER #4

VESSELS

5	51	CRUDE TOWER
	52	DIESEL DRIER
	53	RAW GAS ACCUMULATOR
	54	DESALTER
	55	SPLITTER TOWER
10	56	SPLITTER ACCUMULATOR
	57	DEPROPANIZER TOWER
	58	DEPROPANIZER ACCUMULATOR
	59	HYDROGEN SEPARATOR
	60	STABILIZER TOWER
15	61	STABILIZER ACCUMULATOR

OTHER

	71	BOILER
20	72	HYDROGEN FLARE


DETAILED DESCRIPTION OF THE INVENTION

25 This process relates to improving the effectiveness of a refinery process catalyst. It is believed this improved effectiveness results because the treatment reduces and/or retards the contamination of the refinery process catalyst. Sources of catalyst contamination are metals, such as lead, iron, vanadium, and nickel, sulfur compounds, arsenic, and coke.

30 The reducing agents used in this process for improving the effectiveness a process catalyst are selected from the group consisting of hydrazine, oximes, hydroxylamines (such as N,N-diethylhydroxylamine),

-8-

erythorbic acid, and mixtures thereof. These reducing agents are described in U.S. Patents 5,213,678 and 4,350,606 which are hereby incorporated by reference. Preferably used as reducing agents are oximes such as the ones described in U.S. Patent 5,213,678 as having the formula:



wherein R_1 and R_2 are the same or different and are selected from hydrogen, lower alkyl groups of 1-8 carbon atoms and aryl groups, and mixtures thereof. Most preferably used as the oxime are aliphatic oximes, particularly methyl ethyl ketoxime.

An effective amount of reducing agent used to improve the effectiveness of the process catalyst will depend somewhat upon the specific result wanted: improvement of the reformer yield, improved yield of high octane gasoline, reduced yield of benzene, reducing or retarding the contamination of the refiner. Actually, all these benefits are interrelated, and it is difficult to relate an effective amount of reducing agent to one of these parameters, or state an exact amount of reducing agent which will relate to all benefits wanted. However, it can be stated in general that an effective amount will range from 5 ppm to 100 ppm of reducing agent based upon the catalyst feed stock, preferably from 50 ppm to 100 ppm. The catalyst feed stock typically consists of splitter bottoms, reformer feed, and process streams entering the reformer catalyst. Preferably the reducing agent is added to the process stream continuously.

-9-

The following detailed operating examples illustrate the practice of the invention in its most preferred form, thereby permitting a person of ordinary skill in the art to practice the invention. The principles of this invention, its operating parameters, and other obvious modifications thereof will be understood in view of the following detailed examples.

EXAMPLES

The following examples will illustrate the use of MEKOR to improve the efficiency of a process catalyst used in the reformer of a refinery and the octane rating of the gasoline coming out of the reformer which is typically operated at temperatures of 500°C to 525°C and is under a pressure of 200 to 300 psig. The process catalyst was a platinum catalyst arranged on a fixed bed. MEKOR was added to the reformer 41-44 to a pressurized naphtha feed line 25. The temperature of the naphtha feed line was about 250 °C to about 300°C.

The refinery used to test the effect of adding MEKOR to a process stream was a small refinery which refines approximately 10,000 barrels of crude oil per day. The diagram of the refinery is shown in Figure 1.

EXAMPLES

Control Examples C1-C3 in Table I show how the catalyst was working in the reformer before adding MEKOR.

Examples 1-2 in Table II show how the addition of 50 ppm MEKOR into the naphtha feed line 25 flowing to the splitter tower 55 affected the effectiveness of the catalyst in terms of hours of operation and output.

-10-

TABLE I (Control)
(Reformer Length of Operation - Before MEKOR Addition)

Control Examples	Start of Run	End of Run	Hours of Operation	Throughput Bbls.
C1	6/21/93	7/27/93	936	66,292
C2	7/31/93	8/22/93	552	34,045
C3	8/28/93	10/5/93	960	64,227
Average			816	54,855

5

TABLE II
(Reformer Length of Operation - After MEKOR Addition)

Example	Start of Run	End of Run	Hours of Operation	Throughput Bbls.
1	10/8/93	1/11/94	2,304	149,125
2	1/16/94	3/26/94	1,668	100,238
3 Average			1,986	124,681

10

A comparison of the data in Tables I and II clearly shows that the addition of MEKOR to the reformer more than doubles the hours of operation and barrels of throughput when MEKOR is added to the naphtha process stream feeding the reformer and comes into contact with the reformer process catalyst.

A sample of the reformate leaving the reformer before and after the treatment is measured for octane rating, benzene, and aniline. Table III, IV, and V show how the reformer was operating relative to these outputs before MEKOR was introduced into the reformer. Table IV shows how the reformer operated after adding 75 ppm of MEKOR to the naphtha stream (feedpoint 25) flowing to the reformer.

25

-11-

TABLE III (Control)
Reformer Catalyst Performance Data
Before MEKOR Addition

Example	Reformer Feed (bpd)	Hours Into Run	Bbls. Thruput Since Startup	Octane $\frac{R+M}{2}$	Aniline	Yield %
C4	1750	168	9837	93.90	-15	77.99
C5	1715	192	11670	93.80	-14	78.57
C6	1647	216	13429	93.50	-11	79.06
C7	1571	240	15108	93.50	-10	79.72
C8	1469	264	16677	93.60	-14	81.09
Avg.	1630			93.66	-12	79.29

5

Table IV
(Reformer Catalyst Performance Data - After MEKOR Addition)

10

Example	Reformer Feed (bpd)	Hours Into Run	Bbls. Thruput Since Startup	Octane $\frac{R+M}{2}$	Aniline	Yield %
3	1550	132	8884	93.00	-12	91.24
4	1550	156	10541	93.00	-10	89.75
5	1335	180	11968	97.00	-25	91.99
6	1606	252	17211	97.00	-20	86.55
7	1573	276	18891	97.00	-20	87.74
Avg.	1523			95.40	-17	89.45

Tables III and IV show the addition of MEKOR increases yield and octane number and decreases the aniline number.

15

-12-

Table V
Benzene Produced From Hydrocracking Reaction

Example	Hexane	MCP	CYH	BZE	Sum C6	BZE from Hydro- Cracking	MEKOR ppm
C10	2.337	0.367	0.030	9.245	9.642	2.508	0.0
10	2.462	1.010	0.045	7.120	8.175	1.041	20.0

5 Table V shows that the addition of MEKOR lowers
the amount of benzene produced from the hydrocracking
reaction. This is significant because future regulations
by the Environmental Protection Agency will limit the
amount of benzene in gasoline to less than one percent by
10 weight. Furthermore, if higher octane gasoline can be
produced in a higher yield with less benzene, undesirable
side reactions will be reduced.

-13-

CLAIMS

We claim:

1. A process for improving the effectiveness of a refinery process catalyst which comprises:
5 treating said refinery process catalyst with an effective amount of a reducing compound selected the from the group consisting of hydrazine, oximes, hydroxylamines, carbohydrazide, erythorbic acid, and
10 mixtures thereof.
2. The process of claim 1 wherein said process catalyst is a catalyst used in the reformer of a refinery operation.
15
3. The process of claim 2 wherein the reducing agent is contacted with refinery process catalyst by feeding the reducing agent through a refinery process stream selected from the group
20 consisting of stripper steam, crude overhead, naphtha, splitter feed, refining feed, and chloriding chemicals used in the reformer.
4. The process of claim 3 wherein the catalyst is a platinum catalyst.
25
5. The process of claim 4 wherein said reducing agent is an oxime.
- 30 6. The process of claim 5 wherein the amount of reducing agent used is from 5 ppm to 100 ppm based upon the weight of the catalyst feed stock.

-14-

7. The process of claim 6 wherein the oxime is fed into the naphtha stream.

5 8. The process of claim 7 wherein the oxime is methyl ethyl ketoxime and said methyl ethyl ketoxime is used is an amount of from 50 ppm to 100 ppm based upon the weight of the catalyst feedstock.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/06717

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : B01J 38/52, 38/04, 20/34

US CL : 502/27, 55, 20

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 502/27, 55, 20; 208/140

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
Please See Extra Sheet.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category ^a	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,101,444 (BURK ET AL) 18 July 1978, claim 9.	1-8
Y	US,A, 4,190,554 (YAMAUCHI ET AL) 26 February 1980, col. 15, table 3.	1-8
Y	US,A, 3,879,311 (SCHOTT ET AL) 22 April 1975, col. 3, lines 1-10, col. 4, lines 60-66.	1-8
Y	US, A, 5,282,957 (WRIGHT ET AL) 01 February 1994, abstract.	1-8
Y	US,A, 5,100,532 (ROLING ET AL) 31 March 1992, abstract, col. 1, lines 30-56.	1-8
Y	US,A, 4,551,226 (FERN) 05 November 1985, abstract.	1-8

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

Special categories of cited documents:	
A document defining the general state of the art which is not considered to be of particular relevance	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to underpin the principle or theory underlying the invention
E earlier document published on or after the international filing date	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
O document referring to an oral disclosure, use, exhibition or other means	*Z* document member of the same patent family
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

23 JUNE 1995

Date of mailing of the international search report

07 AUG 1995

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Authorized officer

SEKIR L. YILDIRIM

Facsimile No. (703) 305-3230

Telephone No. (703) 305-3586

Form PCT/ISA/210 (second sheet)(July 1992)α

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/06717

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A, 5,243,063 (DEVICARIS ET AL) 07 September 1993, abstract.	1-8
Y	US, A, 5,213,678 (RONDUM ET AL) 25 May 1993, abstract.	1-8

Form PCT/ISA/210 (continuation of second sheet)(July 1992)*

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/06717

B. FIELDS SEARCHED

Electronic data bases consulted (Name of data base and where practicable terms used):

APS

search terms: methyl ethyl ketoxime? catalyst? reactivat? regenerat? restor? activity rehabilitat? decontaminat? remov?
contaminant? hydrazine? carbohydrazide? ethyboric? hydroxylamine?